MDI 600-1000W

MDI 600-1000W Series DC DC Isolated Converters Modules



特性 Features

- 超高电压输入 Ultra-high voltage input
- 2倍电压输入 2times input voltage
- 安装方便、单端出线 Easy installation, single side pin out
- 外形美观、散热效果好 Good appearance, good heat dissipation
- 高低电压输入可选 High and low input voltage for option

条件：除特殊指定外，所有参数测试条件为：室温25°C,标称输入电压，纯阻性标称负载
Condition: All specifications are tested under the room temperature 25°C, Normal input voltage and pure resistive normal load.

输入特性 Input Characteristic

额定值 (Rated)	电压范围 (Voltage Range)	额定值 (Rated)	电压范围 (Voltage Range)
12 VDC (额定值 Rated)	18-36 VDC	110 VDC (额定值 Rated)	66-154 VDC
24 VDC (额定值 Rated)	36-72 VDC	600 VDC (额定值 Rated)	400-800VDC

输出特性 Output Characteristic

电压精度 (Voltage Set-point Accuracy)	± 2%
电压调整率(主路) (Line Regulation<main>)	± 0.5%
负载调整率(主路) (Load Regulation<main>)	± 0.5%
电流限制点 (Output Current Limiting)	120%(Typ)

输出电流 (Output Current)	5-60A 任选 (For option)
输出电压 (Output Voltage)	12-110V 任选 (For option)
功率 (Power)	600-1000W

一般特性 General Characteristic

工作频率 (Switching Frequency)	100-200KHz		环境特性 (Environmental Characteristics)	工作壳温 (Case Temperature)	(工业品) Industry -25 – +85°C (军I) Military I -40 – +85°C (军II) Military II -55 – +85°C
绝缘电阻 (Isolation Resistance)	200MΩ				
绝缘强度 (Isolation Voltage)	输入-输出 (Input-Output)	>1500VDC		存储温度 (Storage Temperature)	(工业品) Industry -45 – +105°C (军I) Military I -55 – +105°C
	输入-外壳 (Input-Case)	>1050VDC			
	输出-外壳 (Output-Case)	>500VDC			

保护特性 General Characteristic

- ★ 输入欠压保护(Input under voltage protection)
- ★ 过温保护(Over temperature protection)
- ★ 输出过流保护(Output over current protection)
- ★ 输出短路保护(Output short circuit protection)

	输入电压(Vdc) Input voltage	输入电压范围（Vdc） Input voltage Range	输出电压（Vdc） Output voltage	输出电流（A） Output current(A)	纹波PK-PK（mv） Ripple and noise	效率(Typ) Efficiency(Typ)	型号 Models
单路 Single Channels Output	24	18-36	27	37	200	88%	MDI1000-24S27
	48	36-72	24	41.6	200	89%	MDI1000-48S24
	110	66-154	110	9.1	600	89%	MDI1000-110S110
	110	66-154	48	20.8	300	89%	MDI1000-110S48
	600	400-800	24	41.6	200	89%	MDI1000-600S24
	600	400-800	110	9.1	400	89%	MDI1000-600S110

■说明1：输出纹波噪声（峰值-峰值）采用的是87-88页附录四模块电源测试说明
Output ripple noise (Peak-Peak) is adopted the module power supply test instruction on the page 87-88.

■说明2：仅列出典型型号，其它型号，请确定功率、输入电压及输出电压，致电我公司 400-019-3997
Only typical models listed. If you need other model, please conform the power, input voltage and output voltage, then phone us +86 400-019-3997

外形尺寸以及引脚定义 Mechanical drawing and pin definition



单位(Unit):mm

引脚 PIN	单路 SING	输入≥48V SING
1	-Vin	-Vin
2	-Vin	NC
3	-Vin	+Vin
4	+Vin	NC
5	+Vin	Gr.
6	+Vin	NC
7	-VO	-VO
8	-VO	-VO
9	+V0	+V0
10	+V0	+V0