XDB 350-500W

XDB 350-500W New Energy Batteries Power Series
DC-DC Isolated Converters



特性 Features

- 高低电压输入可选 High and low voltage input is for option
- 2倍电压输入 2X，voltage input
- 输出短路保护 Output short circuit protection
- 安装方便 Easy installation
- 高可靠性，长寿命设计 Design for high reliability ,long lifetime
- 支持恒压恒流充电 Can be charged with constant voltage and current

条件：除特殊指定外，所有参数测试条件为：室温25°C,标称输入电压，纯阻性标称负载
Condition: All specifications are tested under the room temperature 25°C, Normal input voltage and pure resistive normal load.

输入特性 Input Characteristic

额定值 (Rated)	电压范围 (Voltage Range)	额定值 (Rated)	电压范围 (Voltage Range)
12 VDC (额定值 Rated)	9-18 VDC	48 VDC (额定值 Rated)	36-72 VDC
24 VDC (额定值 Rated)	18-36 VDC	110 VDC (额定值 Rated)	66-154 VDC
		600 VDC (额定值 Rated)	400-1800 VDC

输出特性 Output Characteristic

电压精度 (Voltage Set-point Accuracy)	± 2%
电压调整率(主路) (Line Regulation<main>)	± 0.5%
负载调整率(主路) (Load Regulation<main>)	± 0.5%
温度变化率 (rate of change of temperature)	±0.01%/°C
电流限制点 (Output Current Limiting)	120%(Typ)

输出电流 (Output Current)	5-40A 任选 (For option)
输出电压 (Output Voltage)	5-48VDC
功率 (Power)	350-500W
响应速度 (response time)	400μs

一般特性 General Characteristic

工作频率 (Switching Frequency)	100-200KHz		环境特性 (Environmental Characteristics)	工作壳温 (Case Temperature)	(工业品) Industry -25 – +85°C (军I) Military I -40 – +85°C (军II) Military II -55 – +85°C
绝缘电阻 (Isolation Resistance)	200MΩ				
MTBF	> 500000 h				
绝缘强度 (Isolation Voltage)	输入-输出 (Input-Output)	>1500VDC		存储温度 (Storage Temperature)	(工业品) Industry -45 – +105°C (军I) Military I -55 – +105°C
	输入-外壳 (Input-Case)	>1050VDC			
	输出-外壳 (Output-Case)	>500 VDC			

保护特性 General Characteristic

★ 输入欠压保护(Input under voltage protection)

★ 输入过压保护(Input over voltage protection)

★ 过温保护(Over temperature protection)

★ 输出过流保护(Output over current protection)

★ 输出短路保护(Output short circuit protection)

	输入电压(Vdc) Input voltage	输入电压范围 Input voltage Range	输出电压（Vdc) Output voltage	输出电流（A) Output current(A)	纹波PK-PK（mv) Ripple and noise	效率(Typ) Efficiency(Typ)	型号 Models
单路 Single Channels Output	24	18-36	12	29.1	200	89%	XDB350-24S12
	24	18-36	24	20.8	200	89%	XDB500-24S24
	48	36-72	24	20.8	120	88%	XDB500-48S24
	110	66-154	24	20.8	200	89%	XDB500-110S24
	600	400-800	24	20.8	200	89%	XDB500-600S24
	600	400-800	48	10.4	200	84%	XDB500-600S48
	600	400-800	110	4.5	200	84%	XDB500-600S110

■说明1：输出纹波噪声（峰值-峰值）采用的是87-88页附录四模块电源测试说明
Output ripple noise (Peak-Peak) is adopted the module power supply test instruction on the page 87-88.

■说明2：仅列出典型型号，其它型号，请确定功率、输入电压及输出电压，致电我公司 400-019-3997
Only typical models listed. If you need other model, please conform the power, input voltage and output voltage, then phone us +86 400-019-3997

外形尺寸以及引脚定义 Mechanical drawing and pin definition





单位(Unit)：mm

引脚 PIN	单路 SING	输入≥48 SING	双路 DOU
1	-Vin	Gr.	-Vin
2	-Vin	NC	-Vin
3	+Vin	-Vin	+Vin
4	+Vin	NC	+Vin
5	-Vo	+Vin	-Vo1
6	-Vo	NC	+Vo1
7	+Vo	-Vo	-Vo2
8	+Vo	+Vo	+Vo2